

Riverstone® 1015

Reactive thinner for Riverstone® resins

Application: Riverstone® 1015 is a reactive thinner for Riverstone® pre-coating resins and Riverstone® binders for polymer concrete. Riverstone® 1015 reduces the viscosity.

Technical Data:

Form supplied	liquid	
Density 20 °C	DIN 51757	0,945 g/cm ³
Refractive index, n _d ²⁰	DIN 53491	1,44 – 1,45
Color number	DIN 53409	< 50 APHA
Acid number	DIN 53402	< 1
Viscosity	DIN 53015	~ 1,7 mPas
Outflow time, 20 °C ISO beaker 3 mm	ISO 2431	18 – 20 sec
Flame point	DIN 51755	+ 10 °C
Storage, at least 6 months	dark at	< 20 °C

Form supplied: liquid in tin cans or containers

Processing: The addition of Riverstone® 1015 reduces the viscosity of Riverstone® resins and mixtures. Simultaneous the reactivity of the mixtures is decreased. The maximum dosage rate of Riverstone® 1015 is mentioned on the technical data sheet of the respective resin.

Plasti-Chemie GmbH

Falgardring 1
D-08223 Falkenstein

Telephone +49/37 41 55 83-0

Fax +49/37 41 55 83-27