

DECLARATION OF PERFORMANCE Plastipur® 570

According Annex III of Regulation (EU) Nr. 305/2011

Name of product:

Plastipur® 570

Nr. PF570-00 1

1. Unique identification code of product-type:

EN 13813: SR-C35/45-F29-B2,0-AR0,5-IR12 EN13501-1: E_{fl}

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

EN 13813 Synthetic resin

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to article 11 (5):

Plasti-Chemie Produktionsgesellschaft mbH Falgardring 1 D-08223 Falkenstein Germany

5. Where applicable, name and contact address of the authorized representative whose mandate convers the tasks specified in article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in annex V:

EN 13813:

System 4 (for application in buildings)

Telefon: +49 (0) 3745 / 74432-0

Telefax: +49 (0) 3745 / 74432-27

Email: info@plasti-chemie.de



DECLARATION OF PERFORMANCE Plastipur® 570

According Annex III of Regulation (EU) Nr. 305/2011

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Not relevant

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared Performance: EN 13813:

Table 2: Declared performance according to EN 13813

		Harmonized
Essential characteristics	Performance	technical specification
Reaction to fire	Efl	
Release of corrosive substances	SR	
Water penetration	NPD	
Abrasion resistance	≤ AR0,5	
Bond strength	≥ B2,0	
Impact resistance	≥ IR12	EN 13813:2002
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical substances	NPD	
Compressive strength	C40	
Bending tensile strength	F20	

10. The performance of the product identified in points 1 and 2 is conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Volkmar Lull (General Manager)

Telefon: +49 (0) 3745 / 74432-0

Telefax: +49 (0) 3745 / 74432-27

Falkenstein, 01.10.2022

(Place and date of exhibition)

(Signati/r/2)

Email: info@plasti-chemie.de