

Application: Plastifloor®- A cleaner is a solvent that, due to its aggressive dissolving power, is capable of dissolving even cured PMMA layers.

Characteristics: Plastifloor®-This cleaner is a low-boiling solvent with excellent solvency. It is highly flammable. It is suitable for cleaning tools and soiled components.

The resistance of the materials to be treated must always be tested beforehand. Plastifloor® Cleaner is not suitable for diluting Plastifloor® coating resins. Clean equipment before curing occurs, whenever possible.

Properties of the delivered product:

Form of delivery	Liquid, colorless
Shelf life	dark at < 20 °C
Delivery Container	155 kg Drum , 25 kg Bucket, 5 kg Canister

Cleaner-Base:

- Plastifloor®- Acetone-based cleaner
-Plastifloor®- Ethyl acetate-based cleaner
- Plastifloor®- MMA-based cleaner

Safety Instructions: The cleaner is low-boiling and highly flammable (A I). Adequate ventilation must always be ensured during application. Open flames, smoking, and spark generation from tools must be strictly avoided, as vapor-air mixtures can explode.

Processing: Plastifloor® Use the cleaner in accordance with the application instructions. Apply the product undiluted to the tools to be cleaned and allow it to take effect. Subsequently, absorb with a suitable cloth or wipe off with suitable material. Ensure adequate ventilation during application.

Storage: Store the product in cool, dry, and well-ventilated areas, in its original container, which must be clearly labeled and tightly sealed. Avoid high temperatures and direct sunlight. Flammable mixtures may form in emptied containers. Provide a spill containment tray without a drain. Store separately from oxidizing agents. Store only outdoors or in explosion-proof areas.

Occupational Safety:

Ensure adequate ventilation during processing. The regulations of the LAsI (State Committee for Occupational Safety) must be observed. Please read and follow the instructions provided in our safety data sheets.

VbF :

A I

HS-Code:

2914 1100

CE
Plasti Chemie Produktionsgesellschaft mbH • Falgarding 1 • 08223 Falkenstein • Germany
EN 13813, SR-B2, 0-AR0, 5-IR12
Plastifloor® Cleaner
Application in accordance with the latest technical information

CE- Labeling

Our information regarding our products, equipment, systems, and processes is based on extensive development work and practical application experience. We provide these findings—for which we assume no liability extending beyond the scope of the respective individual contract—both verbally and in writing to the best of our knowledge; however, we reserve the right to make technical modifications in the course of product development. Nevertheless, this does not absolve the user of the responsibility to independently verify the suitability of our products and processes for their own specific application. This also applies with regard to the observance of third-party intellectual property rights, as well as to applications and procedures that have not been expressly authorized by us in writing.

20.05.2026

2 /2