

**STATEMENT OF SERVICES**

in accordance with Annex III to Regulation (EU) No. 305/2011  
as amended by Delegated Regulation (EU) No. 574/2014

For the product:  
Plastifloor® 050/051

---

Synthetic resin mortar system for high-traffic surfaces  
No. 050/051-00 2

---

**1.Unique identification code for the product type:**

EN 13813: SR-C70-F20-B2,0-AR0,5-IR12  
EN 13501-1 : Efl

---

**2.Type, lot, or serial number, or any other identifier used to identify the construction product in accordance with Article 11(4):**

Lot number: See the product packaging

---

**3. Intended Use(s):**

EN 13813  
Synthetic resin screed for indoor use  
(The system configurations specified in the respective technical documentation must be followed)

---

**4. Manufacturer:**

**Plasti-Chemie International GmbH**  
**Falgardring 1**  
**08223 Falkenstein**

---

**5. If applicable, the name and contact address of the authorized representative responsible for the duties specified in Article 12, paragraph 2 :**

not relevant

---

**6.Harmonized Standard :**

EN 13813:2002

---

**6. System or systems for assessing and verifying the consistency of the construction product's performance in accordance with Annex V:**

System 4

**7. In the case of a declaration of performance concerning a construction product covered by a harmonized standard:**

not relevant

**8. In the case of a declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

not relevant

**9. Declared Service(s):**

| Key Features                    | Performance | System for Evaluating and Verifying Performance Consistency | Harmonized Technical Specification |
|---------------------------------|-------------|-------------------------------------------------------------|------------------------------------|
| Compressive Strength            | C70         | System 4                                                    | EN 13813:2002                      |
| Flexural Tensile Strength       | F20         |                                                             |                                    |
| Adhesive Tensile Strength       | B2,0        |                                                             |                                    |
| Wear resistance                 | AR0,5       |                                                             |                                    |
| Impact Resistance               | IR12        |                                                             |                                    |
| Fire Behavior                   | Efl         |                                                             |                                    |
| Release of corrosive substances | SR          |                                                             |                                    |
| Hazardous Substances            | NPD         |                                                             |                                    |

The performance of the product described above corresponds to the declared performance(s). The manufacturer named above is solely responsible for preparing the declaration of performance in accordance with Regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer by:

Volkmar Lull  
(Managing Director)

Falkenstein, 24.07.2026

  
(Unterschrift)